

|  |  |   |
|--|--|---|
| <p><b>SITA 107</b><br/> Length = 267 mm<br/> Ports = 1/8 in<br/> Wattage - 12w<br/> Flow Rate - 5 L/min</p>           | <p><b>WH10-14 10in Slimline Housing with 1/4in Ports with PS5 5 micron Sediment filter</b></p>  |   |
| <p><b>SITA 403 AL</b><br/> Length = 394 mm<br/> Ports = 1/2 in Male<br/> Wattage - 16w<br/> Flow Rate - 10 L/min</p>  | <p><b>SLH10 Housing with Filter PS5 - 5 Micron Sediment</b></p>                                 | <p><b>VIH10-BL – Housing with Filter PS5 - 5 Micron Sediment 10in Valve in Head</b></p>    |
| <p><b>SITA 405 AL</b><br/> Length = 524 mm<br/> Ports = 3/4 in<br/> Wattage - 30w<br/> Flow Rate - 20 L/min</p>     | <p><b>SLH10 Housing with Filter PS5 - 5 Micron Sediment</b></p>                               | <p><b>VIH10-BL – Housing with Filter PS5 - 5 Micron Sediment 10in Valve in Head</b></p>  |
| <p><b>SITA 405 CAL</b><br/> Length = 674 mm<br/> Ports = 3/4 in<br/> Wattage - 35w<br/> Flow Rate - 30L/min</p>     | <p><b>HD10 – Heavy Duty 10in Housing with PS5 - 5 Micron Sediment Filters</b></p>             |   |

SITA 412 AL  
 Length = 925 mm  
 Ports = 1 in  
 Wattage - 40w  
 Flow Rate - 45 L/min



HF10BB – High Flow 10in with 1in  
 BSP Ports & PS5-10BB Sediment



Filter

SITA 440 AL  
 Length = 880 mm  
 Ports = 1.5 in  
 Wattage - 40w  
 Flow Rate - 60 L/min



HF10BB – High Flow 10in with 1in  
 BSP Ports & PS5-10BB Sediment  
 Filter



**AL/2 Controller – Optional Controller**

- **Optional for SITA UV range 405 to 440 Domestic Range**
- **Days Run Indicator**
- **Lamp Failure/End of Life Audible Alarm**
- **Easy Reset on Bulb Change**
- **Can be used to upgrade Standard Control Box.**