



The Internet Company with a personal touch

Wrekin Water Softeners Stainless Steel UV with (i) Controller range





Model	SSi15	SSi30	SSi55	SSi75	SSi1475	SSi1575
Lamp Power (Watts)	15	30	55	75	75	75
Flow Rate (Litres/Min)	9.5	23	39	60	117	152
Lamp Life (Days)	365	365	365	365	365	365
Control Panel	Type i	Type i	Type i	Type i	Type i	Type i
					1.5" Same	1.5" Same
Standard Connection (MBSP)	3/4"	3/4"	3/4"	1"	Side	Side
Overall Length	455	915	915	1220	1220	1220
Max Pressure (Bar)	10	10	10	10	10	10
Recommended Housing	SLH10/VIH10	SLH10/VIH10	HD10/HF10BB	HF10BB	HF20BB	HF20BB

Control Panels

110v - 240v

Example of Controller for all models (55w system is shown here)








The Internet Company with a personal touch

UV chamber SS1475 same side nipples incl gland nuts









The Internet Company with a personal touch



HD10

10in Heavy Duty Housing with Bracket and spanner and 2 x 3/4in nipples. 3/4in BSP in/out ports.

Suitable for higher flows up to 40 lpm

Available in Twin Housing with single bracket

Height = 330mm Depth/Diameter = 135mm Filter size 2.5in Diameter x 10in Nominal Accepts PS5 Sediment Filter



HF10BB

10in High Flow Housing with Bracket and spanner. 1in BSP in/out Ports

Suitable for systems 40 Lpm – 76 lpm

Height = 260mm Depth/Diameter = 190mm

Filter Sixe 4.5in Diameter x 10in Nominal Accepts PS5-10BB Filter

Available in Twin and Triple housings with single bracket



HF20BB

20in High Flow Housing with Bracket and spanner. 1in BSP in/out Ports.

Suitable for flows up to 97 Lpm

Height = 610mm Depth/Diameter = 190mm

Filter Size = 4.5in Diameter x 20in Nominal Accepts PS5-20BB Filter

Available in Twin and Triple housings with single bracket





The Internet Company with a personal touch

	Standard Sediment Filter – 10in			
	2.5in Diameter x 10in Nominal			
	Fits Standard 10in Housings			
	• SLH10			
	 VIH10 – Valve in head 			
	 HD10 – Heavy Duty Housing 			
	5 Micron rating recommended for UV			
	Order Code = PS5			
	Other Micron Sizes available			
	Other Whereth Sizes available			
	High Flow Sediment Filter			
	4.5in Diameter x 10in Nominal			
	Fits High Flow or Big Blue (BB) Housings			
	HF10BB			
	Fits Any BB 10in Housing			
	The same state of			
	5 Micron rating recommended for UV			
	Order Code = PS5-10BB			
	Order code = 133 10bb			
	Other Micron Sizes available			
	Other Wherom Sizes available			
	High Flow Sediment Filter			
	4.5in Diameter x 20in Nominal			
	Fits High Flow or Big Blue (BB) Housings			
	HF20BB			
	Fits Any BB 20in Housing			
The state of the s	, , , , , , , , ,			
	5 Micron rating recommended for UV			
	Order Code = PS5-20BB			
	0.00.0000 1.00 2022			
	Other Micron Sizes available			





The Internet Company with a personal touch

Optional Add On

The EVC4 Controller controls a Solenoid valve fitted to the outflow of the UV system. The Unit has its own independent power supply and a cable link, (Supplied) back to the SSi Power Supply Unit. The solenoid valve is closed automatically if either the UV Lamp fails or there is a mains power cut.







If you have the original SS/A power supply then you would need to replace this with the SSi PSU with has the communication port on the side to be able to achieve full functionality. Please see picture.